



Key Features

- Web Base IP Camera
- M-JPEG Compression
- Support LAN, Internet and Mobile

IP CAMERA



0.3 LUX

Technical Specifications

Image System

Compression: Motion JPEG hardware compression

Lens Mount: C/CS (With Adaptor)

Min. 2.0 to 3.0 Lux

Automatic Exposure Control

Automatic Gain Control

Automatic Brightness Control

Automatic White Balance

Flicker Avoidance (Flickerless)

Resolution: QVGA (320 x 240) VGA (640 x 480)

Image Frame Rate

Max. 15 fps at QVGA resolution, average 700 kbps/sec

Max. 4 fps at VGA resolution, average 700 kbps/sec

I/O Interface

CAT5, RJ-45 x1 (802.3)

USB1.1

Network Protocols

TCP/IP, HTTP, ARP, ICMP, PPPoE, DHCP, SMTP, DDNS Clients

IE6, NETSCAPE, FIREFOX, SAFARI, EWE, i-mobile by smart etc...

Mechanical & Environment

Dimensions (mm, L x H x W) : 106 x 46 x 46

Weight (g): 250 / 250 (C1001A/ C1001B)

Power Requirement : 5 V / 0.1 to 0.3 A / 1.5 W (max.)

Operation Temp : 5 oC to 50oC (40 oF to 122o F)

Humidity : Rh10 % to 90 %