



IP CAMERA

Pan/Tilt



0.2 LUX



COLOR

Key Features

- Web Base IP Camera
- MPEG-4 simple profile for video, G.726 or AMR for audio
- Support LAN, Internet
- Vertical rotation range 0-90
- Horizontal rotation range 0-325

Technical Specifications

Camera

1/3" solid-state CCD sensor, 420TV lines

f 8.0 mm / F2.0, 0.2 Lux

Audio Support

Frequency 20-20000Hz, S/N ratio more than 55dB.

Adjustable audio data rate, 5Kbps to 40Kbps.

Synchronized video + audio compression.

Image

Image Frame Rate: Up to 25 (PAL) Frames Per Second @CIF, 18 fps @ D1.

Image quality setting: Contrast, Brightness, Saturation, Hue.

Compression: MPEG-4 simple profile for video, G.726 or AMR for audio.

Adjustable video data rate, 64Kbps to 1.8M .

Resolutions: QCIF, CIF, 2 CIF, FULL D1.

PAL Auto detection.

Hardware

Vertical rotation range: 0 - 90.

Horizontal rotation range: 0 - 325.

Auto Pan range: 0 - 325, 16 preset points.

Audio Input: 1 Microphone Jack connector.

Network: One RJ-45 for 10/100 Fast Ethernet.

Alarm: 2 alarm input, 12V DC 50 mA,

1 NC/ NO relay output, Contact rating 3A@125V AC / 30V DC

Physical Features

Power : 12V DC10 %, 700mA

Temperature : -10C - 50C (14F - 122F)

Humidity : 10% - 80%

Dimensions : 154 x 160 x 147 mm (L x W x H)

Weight : 800g

Other Features

Snapshot, Schedule recording.

Simultaneously multiple clients service more than 20Mbps streaming out